



PREMIUM SAND SEPARATOR

The new Premium Sand Separator is designed similar to the Premium Rod Pump Gas Separator to separate free gas, with an added feature that allows it to also separate sand and other sediments from the wellbore liquids, prior to entering the pump.

Centrifugal forces will force the solids to separate towards the inside wall of the separation chamber, while the liquids (clear of solids) will be produced through the central flow tube.

The separated solids will accumulate in the sump attached to the bottom of the separator (i.e. tail pipe). This sump can be periodically cleaned during a pump change or it can be flushed if a Premium Purge Valve is installed at the bottom of the sump.

The Premium Sand Separator can be used in conjunction with Rod Pumps or PC Pumps.

As with our Premium Rod Pump Gas Separator, the Premium Sand Separator is available in either Regular Steel Housing or Stainless Steel Housing configurations. The Stainless Steel housing offers superior protection in corrosive environments and greatly extends the life of the tool.

Minimum Casing Size		Maximum OD		Connections EU*		Production Volumes**	
inch	mm	inch	mm	inch	mm	BPD	m ³ /day
4 1/2"	114.3	3.25"	82.6	2 3/8"	60.3	158	25
5 1/2"	139.7	4.25"	108.0	2 7/8"	73.0	315	50
7"	177.8	5.25"	133.4	2 7/8"	73.0	473	75
7"	177.8	5.25"	133.4	3 1/2"	88.9	473	75

*Premium ALS is pleased to offer other connection sizes and types

**Please contact us if higher production volumes are required