



PREMIUM TWO-WAY TUBING SWIVEL

The Premium Two-Way Tubing Swivel is used in conjunction with tubing rotators to allow the tubing to be rotated during production. The swivel is designed to allow torque anchors to be set and can be easily sheared to allow the tubing to freely rotate in either direction. A couple of unique features are a beveled housing allowing for easier shear screw removal when redressing and a two piece bearing race configuration ensuring smooth and seize free operation.

Tubing Swivel Size		Maximum OD		Minimum ID		Total Length	
inch	mm	inch	mm	inch	mm	inch	mm
2 3/8"	60.3	3.50"	88.9	1.995"	50.7	19.00"	482.6
2 7/8"	73.0	4.20"	106.7	2.441"	62.0	19.50"	495.3
3 1/2"	88.9	5.00"	127.0	2.992"	76.0	19.50"	495.3
4 1/2"	114.3	6.00"	152.4	3.958"	100.5	19.50"	495.3

*Premium ALS is pleased to offer other connection sizes and types

This simple design allows for easy redressing with a Premium Two-Way Tubing Swivel Repair Kit.

PREMIUM TWO-WAY TUBING SWIVEL SLIMHOLE DESIGN

The Premium Two-Way Tubing Swivel also comes in a Slimhole design for applications where a smaller OD is required. The Slimhole design has all the same features as the regular design and can be redressed with a Premium Two-Way Tubing Swivel Slimhole Repair Kit.

Tubing Swivel Size		Maximum OD		Minimum ID		Total Length	
inch	mm	inch	mm	inch	mm	inch	mm
2 3/8"	60.3	3.20"	81.3	1.995"	50.7	19.00"	482.6
2 7/8"	73.0	3.875"	98.4	2.441"	62.0	19.50"	495.3
3 1/2"	88.9	4.50"	114.3	2.992"	76.0	19.50"	495.3
4 1/2"	114.3	5.75"	146.1	3.958"	100.5	19.50"	495.3

*Premium ALS is pleased to offer other connection sizes and types